



IZLT8.E46754 Fuseholders, Cartridge Fuse Certified for Canada - Component

If you notice a change to your IZLT8 Listing Card, click [here](#) to learn more.

[Page Bottom](#)

Fuseholders, Cartridge Fuse Certified for Canada - Component

[See General Information for Fuseholders, Cartridge Fuse Certified for Canada - Component](#)

ECHO ELECTRIC CO LTD

E46754

621 NAGAI

YATSUSHIRO-CHO

FUEFUKI-SHI, YAMANASHI 406-0823 JAPAN

Cat. No.	Voltage Rating (V)	Current Rating (A)	Withstand Rating RMS Symmetrical	Fuse Class or Size
FC-02NB followed by any two digit numbers, followed by C, may be followed by - M or 2P thru - 30P				
	250ac	10	-	20mm by 5.2mm diameter
FC-03NB followed by any two digit numbers, followed by C, may be followed by - M or 2P thru - 30P				
	250ac	10	-	30 mm by 6.4 mm diameter
FC-03PB followed by any two digit numbers, followed by C, may be followed by - M or 2P thru - 30P				
	250ac	10	-	30 mm by 6.4 mmdiameter
FC-04FB followed by any two digit numbers, followed by C, may be followed by - M or 2P thru - 30P				
	250ac	10	-	30 mm by 6.4 mm diameter
FC-04NB followed by any two digit numbers, followed by C, may be followed by - M or 2P thru - 30P				
	250ac	10	-	30 mm by 6.4 mm diameter
FH-001	250ac/dc	15	-	31.8 mm by 6.4 mm diameter
FH-001AF	250ac	15	-	20 mm by 5.2 mm diameter
FH-002	250ac/dc	10	-	31.8 mm by 6.4 mm diameter
FH-031	250ac/dc	10	-	31.8 mm by 6.4 mm diameter
FH-032	250ac/dc	10	-	31.8 mm by 6.4 mm diameter
FH-032AF	250ac	15	-	31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter
FH-033	250ac/dc	10	-	20 mm by 5.2 mm diameter
FH-042	250ac/dc	10	-	31.8 mm by 6.4 mm diameter
FH-043	250ac/dc	10	-	20 mm by 5.2mm diameter

FH-B01	250ac/dc	15	-	31.8 mm by 6.4 mm diameter
FH-B01F	250ac/dc	15	-	1-1/4 in. (31.8 mm) by 1/4 in. (6.4 mm) diameter
FH-B02	250ac/dc	10	-	20 mm by 5.2 mm diameter
FH-B12	250ac/dc	10	-	20 mm by 5 mm diameter
FH-B13	250ac/dc	10	-	20 mm by 5 mm diameter
FH-S04	250ac	10	-	31.8 mm by 6.35 mm diameter
FH-S07	250ac	10	-	31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter 31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter
FH-S07F	250ac	15	-	31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter
FH-S08	250ac	10	-	20 mm by 5.2 mm diameter
FH-S09	250ac	6	-	20 mm by 5.2 mm diameter
FH-S10	250ac	15	-	31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter
FH-S11	250ac	10	-	31.8 mm by 6.35 mm diameter or 30 mm by 6.4 mm diameter

Marking: Company name or trademark **EDK**, model designation and the Recognized Component Mark for

Canada, 

Last Updated on 2016-11-22

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".