

**WOYR2.E77920**  
**Switches, Special Use - Component**

Enhanced searching capability for this category can be found in UL's IQ Family of Databases ([www.ul.com/iq](http://www.ul.com/iq)).

Page Bottom

**Switches, Special Use - Component**

See General Information for Switches, Special Use - Component

YUASA ELECTRIC CO LTD

E77920

21 NAGAI

YATSUSHIRO-CHO

UEFUKI-SHI, YAMANASHI 406-0823 JAPAN

Cat. No.	Amps	V	Frequency	HP
SC-W1, SC-W2	5/3	125/250	60	—
SC-WL	5/3	125/250	60	—
SE-W2	6/4	125/250	60	—
		to GND		
	6	125	60	—
SF, f/b W, /fb/ followed by 1 thru 5, may be	5/3	125/250	60	—
f/b F, O, P, R, S, T,				
f/b numbers, letters.				
SG	8/6	125/250	60	—
	6/4	125/250	60	—
SJ	10	250	60	—
SN Series	3	250	60	—

Marking: Company name or trademark "EDK", electrical rating and Recognition Mark on switch or smallest container. If marked on the switch, the catalog number may be provided on the smallest unit container.

Cat. No.	Temp C	POL/THR	Per Pole	Endurance	SPCOA
SC-W1, SC-W2	65	1/1 or 2	—	6K	See Note 1

Note 1: The quick-connect tab has not been tested with a female connector, and the suitability of the combination should be considered in the end-use application.

Cat. No.	Temp C	POL/THR	Per Pole	Endurance	SPCOA
SC-WL	65	1/1 or 2	—	6K	2
SE-W2	65	2/1	—	6K	3, See
					Notes 1,2,3
SF, f/b W, f/b 1 thru 5, may be	65	1/1 or 2	—	6K	See Note 3
f/b F, O, P, R, S, T,					
f/b numbers, letters.					
SG	65	2/1 or 2	PP	10K	See Note 4
	65	2/No or NC	PP	10K	See Note 4
SJ	65	2/1	—	10K	See Note 3
SN Series	85	2/1	PP	6K	—

Note 1: The quick-connect tab has not been tested with a female connector, and the suitability of the combination should be considered in the end-use application.

Note 2: The suitability of the actuator button material as an enclosure has not been investigated.

Note 3: The switches provided with terminals that are to be used for printed circuit board connection have not been investigated as part of this report. The suitability of these terminals should be evaluated for compliance with the end-use product standard.

Note 4: These switches have a contact gap of 3 mm or more.

Last Updated on 2005-08-26

Questions?

Notice of Disclaimer

Page Top

Copyright © 2009 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

